



STACLEAN CLEANROOM PAPER CONDUCTIVE

- Electric conductivity: $10^6 \Omega$ or less
 - Suitable for copying
 - Recyclable

Effective against static electricity during manufacturing process and product delivery.

Used as insertion paper for wafer, PCB, chip tray and other electronic products.

Electric characteristics (Measurement environment: 20°C, 30% RH)

Surface resistivity (Ω) *1	Face	1×10^5
	Back	$1,3 \times 10^5$
Volume resistivity (Ω/cm^3) *1		$1,19 \times 10^3$
Half volume period of static electricity (sec.) *2	Face	L.T. 0.1
	Back	L.T. 0.1

Measured values – not guaranteed

*1 Measured by Loresta AP

*2 Measured by STAIRC HONESTMETER TYPE S-5109 after charging 10KV voltage

Dissolution test



10 min. after
mixing

Water resolution
down 10 times

Almost completely resolved. Recyclable as standard NEW STACLEAN RC.

Test method:

Put 40g of 2cm by 2cm square paper in 2 liters of water at room temperature and mix them by TAPPI standard resolution test equipment. Check duration time of complete resolution.

Art.-no.:	Size:	Packaging unit:
RPSCAS72A4	A4	5 x 250 sheets
RPSCAS72A3	A3	5 x 250 sheets

hans j. michael gmbh

Gewerbegebiet Hart 11, D-71554 Weissach i.T., Phone: 0049-7191-9105-0, Fax: 0049-7191-9105-19

e-mail: office@hjm-reinraum.de, website: <http://www.cleanroom-hjm.com>